

McCordsville, Indiana

Town Standards

DIRECTIONS FOR USE

- 1.) The entire set of full size drawings shall be attached to the construction drawings and shall be considered part thereto. A partial set may be used for small projects when whole sections are not applicable. Approval of use of a partial set will be made by the Town Engineer at the time of approval of the construction drawings.
- 2.) Details prepared by outside sources shall not be included in the construction drawings when the said drawings cover work which is covered by McCordsville Standards.
- 3.) Individual McCordsville Standards that do not apply may be crossed out by the design engineer through placement of a single large X over the detail. Minor reference notations may be placed adjacent to individual standard titles for coordination. However, the standards themselves shall not be modified in any way.
- 4.) Details prepared by outside sources covering work which is not covered by the McCordsville Standards are the sole responsibility of the design engineer and shall be placed on sheets other than the McCordsville Standards.





GENERAL NOTES

- 1.) Contractor shall verify the exact location of all existing utilities at least 48 hours prior to any construction or excavation. All utilities shall be adequately supported to minimize damage. The contractor shall be responsible for repairing damaged utilities to the satisfaction of the Town of McCordsville and the owner of the utility.
- 2.) All benchmarks and elevations shall be from NAD 1983 (Conus) Datum. All coordinates shall conform with the Hancock County GIS standard.
- 3.) Wherever proprietary equipment is specified, all proposals for substitution shall be submitted in writing to the Town Engineer and shall be subject to the findings of the Town Engineer and may be appealed to the Public Works Committee.
- 4.) Whenever trench opening encroaches within 5 feet of an existing or proposed street or sidewalk, "B"-Borrow compacted in accordance with the most recent INDOT standard specifications shall be required. Approved backfill may be used under proposed sidewalks provided sidewalks are constructed six months after backfilling of the trench.
- 5.) Installation of or provisions for installation of all underground utilities (including service laterals) to be placed under pavement areas shall be established prior to the construction of pavements including lime stabilization.

REVISION LOG

SHEET NO.	SHEET DESCRIPTION	ISSUED	REVISED	REVISED	REVISED	REVISED
SHEET 1	DIRECTIONS FOR USE, GENERAL NOTES & REVISION LOG	06/14/05				
SHEET 2	RIGHT-OF-WAY SECTIONS & PAVEMENT SPECIFICATIONS	06/14/05				
SHEET 3	RIGHT-OF-WAY DETAILS	06/14/05				
SHEET 4	UTILITY LOCATION GUIDELINES	06/14/05				
SHEET 5	DRIVE WAYS, SIDEWALKS, AND HANDICAP RAMPS	06/14/05				
SHEET 6	STORM SEWER STRUCTURE DETAILS	06/14/05				
SHEET 7	STORM SEWER BEDDING DETAILS AND GENERAL NOTES	06/14/05				
SHEET 8	SANITARY SEWER SPECIFICATIONS	06/14/05				
SHEET 9	SANITARY SEWER DETAILS	06/14/05				
SHEET 10	SANITARY SEWER LIFT STATION STANDARDS & GUIDELINES	06/14/05				

TOWN OF McCORDSVILLE



	TOWN COUNCIL PRESIDENT
	PUBLIC WORKS CHAIRMAN
	TOWN MANAGER
	PUBLIC WORKS COMMISSIONER

HOLEY MOLEY SAYS

"DIG SAFELY"



"IT'S THE LAW"
CALL 2 WORKING DAYS BEFORE YOU DIG
1-800-382-5544
CALL TOLL FREE
PER INDIANA STATE LAW IC8-1-26,
IT IS AGAINST THE LAW TO EXCAVATE
WITHOUT NOTIFYING THE UNDERGROUND
LOCATION SERVICE TWO (2) WORKING DAYS
BEFORE COMMENCING WORK.

REVISIONS				RECOMMEND FOR APPROVAL  DESIGN ENGINEER	7/12/05 DATE	TOWN OF McCORDSVILLE	SHEET
REV. NO.	DESCRIPTION	DATE				1	
						DIRECTIONS FOR USE, GENERAL NOTES & REVISION LOG	OF 10